

Material Safety Data Sheet



SONIC DYNAMIX PLUS

1. Product and company identification

Product name	: SONIC DYNAMIX PLUS	
Material uses	: 2 cycle lubricant.	
Supplier/Manufacturer	Supplier Consumers' Co-operative Refineries Limited P.O. Box 260; 9th Avenue North Regina, SK S4P 3A1 Canada (306) 721-5353	Manufacturer Consumers' Co-operative Refineries Limited P.O. Box 260; 9th Avenue North Regina, SK S4P 3A1 Canada (306) 721-5353
Code	: 50	
Responsible name	: Atrion Regulatory Services, Inc.	
In case of emergency	: CANUTEC (613) 996-6666	

2. Hazards identification

Physical state	: Liquid. [Oily liquid.]
Odor	: Solvent.
Emergency overview	: WARNING! COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. Combustible liquid and vapor. Irritating to eyes and skin. Keep away from heat, sparks and flame. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Contains material that can cause target organ damage. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry	: Dermal contact. Eye contact. Inhalation. Ingestion.
Potential acute health effects	
Inhalation	: Toxic by inhalation. Inhalation of vapors may cause headaches, nausea, dizziness, narcosis and act as a severe central nervous system depressant; vapors may also be irritating to the eyes, nose, throat and lungs. Irritating to respiratory system.
Ingestion	: May be harmful if swallowed. Vomiting may result in aspiration into lungs causing chemical pneumonitis.
Skin	: Irritating to skin.
Eyes	: Irritating to eyes.
Potential chronic health effects	
Chronic effects	: Contains material that can cause target organ damage.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Target organs	: Contains material which causes damage to the following organs: kidneys, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.
Over-exposure signs/symptoms	
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin	: Adverse symptoms may include the following: irritation redness

2. Hazards identification

- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3. Composition/information on ingredients

Name	CAS number	%
Stoddart solvent	8052-41-3	10 - 30

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : In case of contact, immediately flush eyes with plenty of water for at least 20 minutes. Get medical attention.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Remove contaminated clothing, launder before reusing. Get medical attention if symptoms occur.
- Inhalation** : Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.
- Ingestion** : Do not induce vomiting. Rinse mouth. Give 1/2 glass of milk. Give two glasses of water to drink. If spontaneous vomiting occurs, have victim lean forward so that their head is between their knees. Vomiting may result in aspiration into lungs causing chemical pneumonitis.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

- Flammability of the product** : Combustible liquid and vapor. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. Heat will greatly increase fire and explosion hazards. Increased risk of fire and explosion when combined with strong oxidizer.
- Extinguishing media**
- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam. Cover spill with foam.
- Not suitable** : Do not use water jet. Avoid spraying water directly into storage container due to the danger of boilover.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

5 . Fire-fighting measures

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
calcium
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8). Wear protective equipment including rubber boots.
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Launder contaminated clothing before reuse.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

Canada

Product name

Stoddart solvent

Exposure limits
ACGIH TLV (United States, 1/2007).

 TWA: 525 mg/m³ 8 hour(s)

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Provide mechanical ventilation for confined spaces. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Eyes : Splash goggles.

Skin : Wear chemical resistant clothing if prolonged skin contact is likely.

Respiratory : A respirator is not needed under normal and intended conditions of product use. Wear an appropriate NIOSH approved respirator if concentration levels exceed the safe exposure limits. If exposure levels are not known, wear an air supplied respirator(SCBA).

Hands : Gloves: Neoprene, PVC, vinyl or rubber.

Personal protective equipment (Pictograms)


HMIS Code/Personal protective equipment : x

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

Physical state : Liquid. [Oily liquid.]

Flash point : Closed cup: 42.8°C (109°F)

Color : Blue.

Odor : Solvent.

Melting/freezing point : -30°C (-22°F)

Specific gravity : 0.87

Vapor pressure : Not available.

Vapor density : >1 [Air = 1]

Solubility : Slight Soluble in water.

10 . Stability and reactivity

- Stability** : The product is stable.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Heat will greatly increase fire and explosion hazards. Increased risk of fire and explosion when combined with strong oxidizer. Do not allow vapor to accumulate in low or confined areas.
- Materials to avoid** : Reactive or incompatible with the following materials: oxidizing materials.
- Hazardous decomposition products** : Incomplete combustion might produce carbon oxides, nitrogen, sulfur and calcium.

11 . Toxicological information

Acute toxicity

Product/ingredient name	Species	Dose	Result	Exposure
Stoddart solvent	Rabbit	>3 g/kg	LD Dermal	-
	Rat	>5 g/kg	LD Oral	-

- Inhalation** : Toxic by inhalation. Inhalation of vapors may cause headaches, nausea, dizziness, narcosis and act as a severe central nervous system depressant; vapors may also be irritating to the eyes, nose, throat and lungs. Irritating to respiratory system.
- Ingestion** : May be harmful if swallowed. Vomiting may result in aspiration into lungs causing chemical pneumonitis.
- Skin** : Irritating to skin.
- Eyes** : Irritating to eyes.

12 . Ecological information

- Environmental effects** : No known significant effects or critical hazards.

13 . Disposal considerations


- Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.



14 . Transport information

AERG : 128

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	UN1993	FLAMMABLE LIQUID, N.O.S. (Stoddart solvent)	3	I		-



14 . Transport information

IMDG Class	UN1993	FLAMMABLE LIQUID, N.O.S. (Stoddart solvent)	3	I		-
IATA-DGR Class	UN1993	FLAMMABLE LIQUID, N.O.S. (Stoddart solvent)	3	I		-

PG* : Packing group

15 . Regulatory information

Canada

WHMIS (Canada)

- : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
- Class D-2B: Material causing other toxic effects (Toxic).



Canadian lists

- : **CEPA Toxic substances:** None of the components are listed.
- Canadian ARET:** None of the components are listed.
- Canadian NPRI:** The following components are listed: Stoddart solvent
- Alberta Designated Substances:** None of the components are listed.
- Ontario Designated Substances:** None of the components are listed.
- Quebec Designated Substances:** None of the components are listed.

Canada inventory (DSL/NDL)

- : **Canada inventory:** All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists

- : This product, (and its ingredients) is (are) listed on national inventories, or is (are) exempted from being listed, in Australia (AICS), in Europe (EINECS/ELINCS), in Korea (TCCL), in Japan (METI), in the Philippines (RA6969).

16 . Other information

Label requirements

- : COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

Hazardous Material Information System (U.S.A.)

:

Health	*	2
Fire hazard		2
Physical Hazard		0
Personal protection		X

HAZARD RATINGS

4- Extreme
3- Serious
2- Moderate
1- Slight
0- Minimal

See section 8 for more detailed information on personal protection.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

:

16 . Other information



References	: ANSI Z400.1, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. - Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2005.
Date of issue	: 06/01/2009
Date of previous issue	: 05/01/2008
Version	: 2

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.